

JBC141F9HB

Desktop Network Embedded Barebone N2930 / 4 or 8 Intel GbE / LAN Bypass



Features

- Desktop Networking mbedded Barebone System
- Intel Celeron N2930 Quad-Core SoC
- Supports DDR3L-1333 SODIMM up to 8GB Total
- 2 * 2.5" SATA2 3Gb/s Internal Drive Bays
- 1 * Full-size mSATA, 4 or 8 Intel Gigabit LAN Ports
- Up to 3 pairs of LAN Bypass
- 1 * Full-size mini-PCIE Slot (or WIFI Installed)
- 1 * USB 3.0 Port, 1 * USB 2.0 Port
- 2 * Serial Ports (1 * RS232/422/485, 1 * RS232)
- VGA Port Installed, optional GPIO/COM cables Included
- Watchdog Timer, 60W 12V AC Adapter
- Dimensions: 44 x 192 x 330mm

FRONT



(Shown with optional 2nd COM, GPIO, and 8-port LAN installed)

REAR



(Shown with optional WIFI antenna installed)

Model	<ul style="list-style-type: none"> JBC141F9HB
Part No	<ul style="list-style-type: none"> 4-LAN - HBJC141F9HB04-29B (1-pair bypass, No WIFI), HBJC141F9HBW4-29B (1-pair bypass, WIFI) 8-LAN - HBJC141F9HB08-29B (1-pair bypass, No WIFI), HBJC141F9HBW8-29B (1-pair bypass, WIFI) 8-LAN - HBJC141F9HB08B29B (3-pair bypass, No WIFI), HBJC141F9HBW8B29B (3-pair bypass, WIFI)
Processor	<ul style="list-style-type: none"> Intel Celeron N2930 SoC Quad-core 1.83GHz processor, 2.16GHz Burst, 7.5 TDP
Memory	<ul style="list-style-type: none"> 2 * 204-pin SO-DIMM slots supporting DDR3L-1333 up to 8GB total
Storage	<ul style="list-style-type: none"> 2 * 2.5" SATA2 3Gb/s internal drive bays, 1 * Full-size mSATA slot
Network	<ul style="list-style-type: none"> 4 or 8 * Intel i211-AT Gigabit LAN, up to 3-pairs LAN bypass 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model), SIM Card Holder
Other Feature	AHCI, Watchdog Timer 10-255 min/sec., AT/ATX power mode support
Rear Panel I/O	<ul style="list-style-type: none"> Power switch 12V DC-in jack 2 * Antenna holes Grounding screw
Front Panel I/O	<ul style="list-style-type: none"> 1 * USB 3.0 1 * USB 2.0 Power LED, HDD LED 4 * RJ45, VGA 2 * DB9 punchout for COM/GPIO
BIOS	<ul style="list-style-type: none"> AMI UEFI 64Mb Flash ROM
Box Contents	<ul style="list-style-type: none"> 60W 12V AC Adapter, US Power Cord, Manual, DVD Driver disk, COM cable, GPIO cable, VGA cable, (2 * 2dBI 2.4GHz Antenna on WIFI model)
Compliance	<ul style="list-style-type: none"> CE, FCC, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> Operating Temperature 0 - 50° C Storage Temperature -40 - 85° C
Dimensions	<ul style="list-style-type: none"> 192 x 330 x 44mm (DxWxH)
OS Support	<ul style="list-style-type: none"> Windows 7, 8.1, 10, Linux
Warranty	<ul style="list-style-type: none"> 2 Years limited warranty

*Specifications subject to change without notice, not responsible for typographical errors. Does not include Memory, Storage or OS.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com

